

# Preparation unit—Metallic bowl

GC□C, GFC□C, GFR□C, GF□C, GL□C Series



## Ordering code

GC200C	08	M	L	<input type="checkbox"/>	F	1	W	<input type="checkbox"/>	K	
GFC200C	08	M	L	<input type="checkbox"/>	F	1	W	<input type="checkbox"/>	K	
GFR200C	08	M	L	<input type="checkbox"/>	<input type="checkbox"/>	F	1	W	<input type="checkbox"/>	K

Model	
GC200C: G200 Series F.R.L unit(Metallic bowl)	
GC300C: G300 Series F.R.L unit(Metallic bowl)	
GC400C: G400 Series F.R.L unit(Metallic bowl)	
GFC200C: G200 Series FR.L unit(Metallic bowl)	
GFC300C: G300 Series FR.L unit(Metallic bowl)	
GFC400C: G400 Series FR.L unit(Metallic bowl)	
GFR200C: G200 Series filter-regulator(Metallic bowl)	
GFR300C: G300 Series filter-regulator(Metallic bowl)	
GFR400C: G400 Series filter-regulator(Metallic bowl)	

  

Model	Port size
GC200C	06: 1/8"
GFC200C, GFR200C	08: 1/4"
GC300C	08: 1/4"
GFC300C, GFR300C	10: 3/8"
	15: 1/2"
GC400C	10: 3/8"
GFC400C, GFR400C	15: 1/2"

  

Drain type	Adaptable product's series
Blank: Semi-auto drain	GC200C, GC300C, GC400C
M: Manual drain	GFC200C, GFC300C, GFC400C
	GFR200C, GFR300C, GFR400C
A: Automatic drain	GC300C, GC400C, GFC300C
	GFC400C, GFR300C, GFR400C

  

Type code
Blank: Standard
L: Lower pressure ①

  

Code of reverse flow valve
Blank: No reverse flow valve is attached
K: Reverse flow valve is attached

  

Thread type
Blank: PT
T: NPT
G: G

  

Filtering grade
Blank: 40 μm
W: 5 μm

  

Scale
1: MPa
2: psi
3: bar

  

Pressure gauge shape
F: Square
C: Circular

  

Pressure gauge
Blank: Pressure gauge
N: No pressure gauge

  

Accessories	
Product's series	Accessories
GFR200C~400C	Blank: Bracket
	J: No bracket (standard configuration)
Other series	Not code

## Product feature

- The metallic bowl type is upgraded G series. Besides its speciality are the same as G series, it's below speciality:
- The bowl is made of metal. It is radiation-proof, excellent aging characteristic, and which allows for outdoor application.
- Metal bowls are suitable for applications requiring higher pressure or rugged environment.
- Fuss free installation for most applications.

## The corresponding table of Metallic bowl type with standard type

Metallic bowl type	Corresponding standard type
GC200C, 300C, 400C	GC200, 300, 400
GFC200C, 300C, 400C	GFC200, 300, 400
GFR200C, 300C, 400C	GFR200, 300, 400
GF200C, 300C, 400C	GF200, 300, 400
GL200C, 300C, 400C	GL200, 300, 400

Note)  
The style, pressure chart, flow chart, Inner structure, dimension etc, are the same as standard type. Please refer to relevant content for details.

## GF200C 08 M □ W □

Model	
GF200C: G200 Series Filter(Metallic bowl)	
GF300C: G300 Series Filter(Metallic bowl)	
GF400C: G400 Series Filter(Metallic bowl)	

  

Model	Port size
GF200C	06: 1/8"
	08: 1/4"
GF300C	08: 1/4"
	10: 3/8"
	15: 1/2"
GF400C	10: 3/8"
	15: 1/2"

  

Thread type
Blank: PT
T: N
G: G

  

Filtering grade
Blank: 40 μm
W: 5 μm

  

Accessories
Blank: Bracket
J: No bracket(standard configuration)

  

Drain type	Addable product's series
Blank: Semi-auto drain	GF200C, GF300C
M: Manual drain	GF400C
A: Automatic drain	GF300C, GF400C

## GL200C 08 □ □

Model	
GL200C: G200 Series Lubricator(Metallic bowl)	
GL300C: G300 Series Lubricator(Metallic bowl)	
GL400C: G400 Series Lubricator(Metallic bowl)	

  

Model	Port size
GL200C	06: 1/8"
	08: 1/4"
	08: 1/4"
GL300C	10: 3/8"
	15: 1/2"
GL400C	10: 3/8"
	15: 1/2"

  

Thread type
Blank: PT
T: NPT
G: G

  

Accessories
Blank: Bracket
J: No bracket(standard configuration)

